

FAQs

1. What is polymer concrete

- No-Fines Concrete is a method of producing light concrete by **omitting the fines** from conventional concrete.
- No-fines concrete as the term implies, is a kind of concrete from which the fine aggregate fraction has been omitted.
- This concrete is made up of **only coarse aggregate, cement and water**.
- Very often only single sized coarse aggregate, of size passing through 20 mm retained on 10 mm is used.
- No-fines concrete is becoming popular because of some of the advantages it possesses over the conventional concrete. The single sized aggregates make a good no-fines concrete, which in addition to having large voids and hence **light in weight**, also offers **architecturally attractive look**.

2. Discuss properties of polymer concrete

- **It does not segregate**
- The density varies with the grading of aggregates
- Water cement ratio of this concrete varies from 0.38 to 0.52
- **Its strength increases with time**
- There is very little cohesiveness, necessitating **longer duration of form work removal**.
- Shrinkage of this concrete is lower than normal concrete and its thermal expansion is about 0.6 to 0.8 of normal concrete.

3. What is ready mix concrete

- Production of this type of concrete results in saving of material requirement. Due to absence of fine aggregate or sand, less amount of cement is needed to produce 1 m³ of no fines concrete.
- The density of this type of concrete is about 25 to 30% less than the conventional concrete. Therefore it exerts less pressure on formwork
- Segregation property of this type of concrete is very low. Therefore it can be dropped from considerable height without the danger of segregation.
- No special equipment is needed for compaction of this concrete. Full compaction can be achieved by simple rodding operation.

4. What is aerated concrete

- Plain Portland cement concrete is a brittle material. The **strength of concrete in tension is much lower than in compression**. A growing tensile crack in plain concrete can very soon lead to failure. In the presence of reinforcement, the tensile load is transferred to the steel.
- An alternative to increasing the load carrying capacity of concrete in tension is the **addition of fibers**. Well-dispersed fibers in the concrete act to bridge the cracks that develop in concrete. The incorporation of fibers in a cement matrix leads to an **increase in the toughness and tensile strength**, and an improvement in the cracking and deformation characteristics of the resultant concrete

5. Write about properties of aerated concrete

- Improve mix cohesion, improving pump ability over long distances
- Improve freeze-thaw resistance
- Improve resistance to explosive spalling in case of a severe fire
- Improve impact resistance– and abrasion–resistance
- Increase resistance to plastic shrinkage during curing
- Improve structural strength
- Reduce steel reinforcement requirements
- Improve ductility
- Reduce crack widths and control the crack widths tightly, thus improving durability